

**Product Name**

Date of issue: Apr. 2021

Revision No : 4

EMPEYOL E4022

**Product Description**

EMPEYOL E4022 is a 4000 molecular weight dihydroxy polyether polyol containing a high percentage of primary hydroxyl groups. It is used extensively in elastomer, coatings, adhesives and sealants, in prepolymers as well as in one shot formulations. It is also used in micro cellular polyurethanes and in blends with high functionality polyols for semi rigid foams.

**Specifications (as per IS: 13702-1993)**

S. No.	Characteristics	Unit	Specification
1	Appearance	----	Clear ,viscous liquid
2	Density at 25 °C	g/cc	1.015 – 1.025
3	Viscosity at 25 °C	Cps	750± 100
4	Colour	APHA	100 maximum
5	Hydroxyl Number	mg KOH/g	27.0 – 29.0
6	Water	% w/w	0.10 maximum

**Packaging Size**

210 / 25 kg nett.

**Storage  
and  
Handling**

- EMPEYOL E4022 polyol is to be stored in tightly closed containers preferably at temperatures between 20 – 35 °C.
- Should wear gloves and goggles during handling.
- Shelf life : 1 year

**Health and  
Safety Advice**

EMPEYOL E4022 polyol should present no unusual health problems when used in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with the skin.

The information in this data sheet is believed to be accurate but all recommendations are made without warranty since the conditions of use are beyond the company's control. MPL disclaims any liability in connection with use of the information and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.