

Date of issue: Apr. 2021  
 Revision No : 4

## Product Name

EMPEYOL R848

## Product Description

EMPEYOL R 848 is a rigid grade base polyol suitable for the formulation of polyol system for Rigid Polyurethane applications.

## Specifications (as per IS: 13702-1993)

S. No.	Characteristics	Unit	Specification
1	Appearance	----	Clear, yellow to brown, viscous liquid
2	Density @25°C	g/cc	1.080 – 1.150
3	Viscosity@25°C	cps	15000 – 20000
4	Colour	Gardner	9 maximum
5	Hydroxyl Number	mgKOH/g	400 – 420
6	Water	% w/w	0.50 maximum
7	Appearance	----	Clear, yellow to brown, viscous liquid

## Packaging Size

210 / 25 kg nett.

## Storage and Handling

- EMPEYOL R848 polyol is to be stored in tightly closed containers preferably at temperatures between 20 – 35 °C.
- Should wear gloves and goggles during handling.
- Shelf life : 1 year

## Health and Safety Advice

EMPEYOL R848 polyol should present no unusual health problems when used in manufacturing operations where satisfactory standards of personal and industrial hygiene are maintained. Precautions should be taken to avoid exposure to the eye or prolonged contact with the skin.

The information in this data sheet is believed to be accurate but all recommendations are made without warranty since the conditions of use are beyond the company's control. MPL disclaims any liability in connection with use of the information and does not warrant against infringement by reason of the use of any of its products in combination with other materials or in any process.